

FREE POINT SPECIFICATIONS



FREE POINT SYSTEMS

FREE POINT SYSTEMS

Tool Diameter	11/16" (17.5mm)	1" (25.4mm)	1 3/8" (35mm)	1 5/8" (41.3mm)
Min Pipe Diameter	1.0" (25.4mm)	1.5" (38.1mm)	1.75" (44.5mm)	1.75" (44.5mm)
Max Pipe Diameter	4.5" (114.3mm)	4.5" (114.3mm)	4.5" (114.3mm)	5.625" (142.9mm)
Tool Length	118" (3m)	137.5" (3.49m)	136.75" (3.47m)	133.5" (3.39m)
Tool Weight	9lbs (4.1kg)	20.5lbs (9.3kg)	38lbs (17.3kg)	50lbs (22.7kg)
Max Temperature	500°F (260°C)	500°F (260°C)	500°F (260°C)	500°F (260°C)
Max Pressure	21,000psi (144 MPa)	21,000psi (144 MPa)	21,000psi (144 MPa)	21,000psi (144 MPa)*

*Note: 1 5/8" HP 30,000 psi (207MPa) Max Pressure



APPLIED
ELECTRONIC
SYSTEMS

a **Sondex** company

www.aesla.com

FREE POINT PRODUCT RANGES

Part No.	Description	Page
----------	-------------	------

1 1/16"

AS1-00FP	1 1/16" Free Point Complete Assy	FP0-3
AS1-00FPM	1 1/16" Free Point Complete with Magnet Section	FP0-3

1"

AS3-00FP	1" Free Point Complete Assy *	FP0-12
AS3-00FPM	1" Free Point Complete with Magnet Section*	FP0-12

1 3/8"

AS4-00FP-16	1 3/8" X 16 Stroke Free Point Complete Assy *	FP0-19
AS4-00FPM	1 3/8" X 16 Stroke Free Point Complete With Magnet Section *	FP0-19


1 5/8"

AS6-00FP-16	1 5/8" X 16 Stroke Free Point Complete Assy*	FP0-26
AS6-00FPM-16	1 5/8" X 16 Stroke Free Point Complete With Magnet Section*	FP0-26

1 5/8" HIGH PRESSURE

AS6-00FPHP-36	1 5/8" X 36 Stroke Free Point Complete Assy*	FP0-33
---------------	--	--------

*Options available



APPLIED
ELECTRONIC
SYSTEMS

a **Sondex** company

www.aesla.com